

Solenoid valves



- ◆ **Burkert**
Brass body, NBR sealings
Temperature range: -10 to + 70°C. 220 Volt

Nr. M180A10 – Closed type without current. High pressure, 1/2" Female thread. 0.2 - 16 bar



- ◆ **ASCO**
Brass body, NBR sealing
Temperature range: -20 to + 50°C. Available in 24 or 220 Volt

- Mountable in any position (coil and connector can be rotated over 360°)
- Water resistant encapsulated coil
- High-tech, low Mass materials ensure a prolonged service life
- Universal fit
- Excellent flow path

Closed type without current

- N° 635-020** 1/2" female thread 0-10 bar - 35 lt/min
- N° 635-030** 3/4" female thread 0-10 bar - 75 lt/min
- N° 635-040** 1" female thread 0-10 bar - 166 lt/min

Open type without current:

- N° 636-030** 3/4" female thread 0-9 bar - 79 lt/min
- N° 636-040** 1" female thread 0-9 bar - 185 lt/min



Repair set

- N° 635-023** for N° 635-030
- N° 635-043** for N° 635-040

1/2" and 3/4" Solenoids

- N° 635-021** 24 Volt
- N° 635-022** 220 Volt

1" Solenoid

- N° 635-041** 24 Volt
- N° 635-042** 220 Volt